



PVC STOP PROFILE J12 WITH TAPE AND PROTECTIVE LIP ETIX 3835 (12,5mm)

The stop beads are designed for the precise finishing of plasterboard in ceiling or wall structures. They ensure a durable and aesthetically pleasing connection to adjacent structures made from different building materials. These beads are used in the installation of plasterboard to secure a firm connection between the boards or with adjacent structures.

Stop Profile	Width (mm)	PE Foam Tape Width (mm)	Length (m)	Packaging (pcs)
ETIX 3835	12,5 mm	8	2,5	56

ADVANTAGES

- Provides an aesthetically pleasing board connection
- Protects the boards from mechanical damage
- The profile edges can cover minor damage to the board ends caused before installation
- Flexible PE foam tape allows for elastic connections with adjacent construction elements
- Flexible PVC protective lip enhances the finishing of the detail

INSTALLATION

Install the PVC stop profile with PE foam tape and protective lip before plastering the wall. The installation surface must be smooth and even. Apply a layer of plaster to the outer surface, then press the PVC stop profile with PE foam tape and protective lip into the plaster. Gradually cover the bead with plaster until a seamless surface with the wall is achieved.

MATERIAL

PVC, Polyethylene Foam Tape, Soft PVC.

STORAGE

Store in a horizontal position. Keep in a dry place and protect from moisture and mechanical stress.