



SEALING TAPE STANDARD

Sealing tape (plasterboard tape KKT) is used in the construction of light partitions, where the part between the metal frame and / or the partition element and the adjacent building structure needs to be sealed or soundproofed.

KKT-S	Length (m)	Width (mm)	Thickness (mm)	Packaging (pcs)
KKT-30-S	30	30	3	32
KKT-50-S	30	50	3	18
KKT-70-S	30	70	3	14
KKT-90-S	30	90	3	12

ADVANTAGES

- Prevents noise transmission
- Good adhesion, convenient, and easy to use
- Resistant to water, saltwater, mold, and oxidation
- Permanently elastic

INSTALLATION

When insulating lightweight partition walls without specific soundproofing requirements, ensure that the surface for applying the KKT-S sealing tape is clean and dry (free of grease, dirt, dust, soot, etc.) before installation. If necessary, remove excess dirt from the frame. Apply the KKT-S tape across the full width of the metal frame. When fixing the frame to the adjacent building structure, the KKT-S will be compressed. Choose the KKT-S width according to the width of the metal frame. For insulating partition elements, place the KKT-S on the surface of the building structure (floor, ceiling, and walls) under the partition board before installation. The tape width should correspond to the thickness of the partition element. The product should be applied when the temperature of the materials and the surface is between +5°C and +40°C.

MATERIAL

Polyurethane.

STORAGE

Store the product in a dry environment, protected from moisture, freezing temperatures, prolonged sunlight exposure, and mechanical stress. Shelf life is up to 12 months.